U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMAR FORM PTO-1390 (Modified) AD6516 TRANSMITTAL LETTER TO THE UNITED STATES U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371 INTERNATIONAL APPLICATION NO. INTERNATIONAL FILING DATE PRIORITY DATE CLAIMED PCT/US98/15229 23 JULY 1998 (23.07.98) 25 JULY 1997 (25.07.97) TITLE OF INVENTION FLAME RETARDANT POLYOLEFIN COMPOSITIONS APPLICANT(S) FOR DO/EO/US GARCIA DURAN, Juan-Antonio et al. Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information 1. This is a FIRST submission of items concerning a filing under 35 U.S.C. 371. This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371. 2. This is an express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1). 3 \boxtimes 4. A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date. \boxtimes \boxtimes A copy of the International Application as filed (35 U.S.C. 371 (c) (2)) 5. is transmitted herewith (required only if not transmitted by the International Bureau). b. □ has been transmitted by the International Bureau. is not required, as the application was filed in the United States Receiving Office (RO/US). A translation of the International Application into English (35 U.S.C. 371(c)(2)). 7 \times A copy of the International Search Report (PCT/ISA/210). Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371 (c)(3)) are transmitted herewith (required only if not transmitted by the International Bureau). have been transmitted by the International Bureau. c. 🗆 have not been made; however, the time limit for making such amendments has NOT expired. \boxtimes have not been made and will not be made. A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)). 10. An oath or declaration of the inventor(s) (35 U.S.C. 371 (c)(4)). 11. A copy of the International Preliminary Examination Report (PCT/IPEA/409). 12. A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371 (c)(5)). Items 13 to 18 below concern document(s) or information included: An Information Disclosure Statement under 37 CFR 1.97 and 1.98. 13. 14. An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included. A FIRST preliminary amendment. A SECOND or SUBSEQUENT preliminary amendment. 16. A substitute specification. 17. \boxtimes A change of power of attorney and/or address letter. 18. \boxtimes Certificate of Mailing by Express Mail 19. Other items or information: 17. General Power of Attorney 18. Express Mailing Label No.: EJ236616789US

430 Hec'd PCT/PTO 1 4 JAN 2000

U.S. A	APPLICATION NO. 11F KNOWN SEE CFR INTERNATIONAL APPLICATION NO. PCT/US98/15229					ATTORNEY'S DOCKET NUMBER AD6516		
20.	The fol	lowing fees are submitted:.						S PTO USE ONLY
		L FEE (37 CFR 1.492 (a) (1) -	(5)):				CIMCOLITIO.	S TTO OSL ORL.
×	-	ort has been prepared by the EPO			\$840.0	00		
	Internationa	preliminary examination fee pai	d to USPTO (37 CFR	1.482)	\$670.00			
	No internation but internation	onal preliminary examination fee onal search fee paid to USPTO (3	paid to USPTO (37 C 37 CFR 1.445(a)(2))	FR 1.482) \$760.0	90		
	Neither interinterinternational	rnational preliminary examination search fee (37 CFR 1.445(a)(2)	n fee (37 CFR 1.482) r paid to USPTO	or	\$970.0	00		
	International and all claim	preliminary examination fee pai is satisfied provisions of PCT Ar	d to USPTO (37 CFR ticle 33(2)-(4)	1.482)	\$96.0	0		
		ENTER APPROPRI	ATE BASIC FE	EE AM	OUNT =	:	\$840.00	
Surcha month	arge of \$130.0 s from the ear	0 for furnishing the oath or declar diest claimed priority date (37 C	eration later than FR 1.492 (e)).	□ 20) 🛮 3	0	\$130.00	
CL	AIMS	NUMBER FILED	NUMBER EXT	`RA	RATI	Ξ		
Total o	claims	6 - 20 =	0		x \$18.0	00	\$0.00	
	ndent claims	1 - 3 =	00		x \$78 (00	\$0.00	
Multi	ole Dependen	t Claims (check if applicable).					\$0.00	
			ABOVE CALC			=_	\$970.00	
Reduc must a	tion of 1/2 for Iso be filed (filing by small entity, if applica Note 37 CFR 1.9, 1.27, 1.28) (ch	eck if applicable).	ntity Stat	ement		\$0.00	
				SUB	FOTAL	=	\$970.00	
Proces month:	sing fee of \$1 s from the ear	30.00 for furnishing the English liest claimed priority date (37 Cl	translation later than FR 1.492 (f)).	□ 20) 🗆 3	0 +	\$0.00	
			TOTAL NAT	IONAI	FEE	=	\$970.00	
Fee for	recording the	e enclosed assignment (37 CFR 1 appropriate cover sheet (37 CFR	.21(h)). The assignme 3.28, 3.31) (check if	ent must b applicabl	e e).		\$0.00	
			TOTAL FEES	ENCL	OSED	=	\$970.00	
							Amount to be: refunded	\$
						l	charged	\$
	A check in	the amount of	to cover the above f	ees is enc	losed.			
Please charge my Deposit Account No. 04-1928 in the amount of \$970.00 to cover the above fees.								
	A duplicate	copy of this sheet is enclosed.						
×	The Commi	ssioner is hereby authorized to cl	narge any fees which n	nay be rec	uired, or cr	edit an	ny overpayment	
	to Deposit A	Account No. 04-1928	A duplicate copy of th	is sheet is	enclosed.			
		appropriate time limit under 37 st be filed and granted to restor				petitio	on to revive (37 CF)	R
SEND	ALL CORRE	SPONDENCE TO:			1	. =	,	
KELI	Y, Patricia	L.			~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~		Part E. Tarma	_
E.I. DU PONT DE NEMOURS AND COMPANY					SIGNATURE Bart E. Lerman Reg. No. 31,897 for			
	AL PATENT MARKET ST	RECORDS CENTER			Patricia			
WILN		DELAWARE 19898			NAME			
US					39,247			
					REGISTR	ATIO	N NUMBER	
					14 JANU	JARY	2000	
					DATE			

WO 99/05214

1

PCT/US98/15229

<u>Title</u>

FLAME RETARDANT POLYOLEFIN COMPOSITIONS

5

Background of the Invention

Field of Invention:

10

This invention relates to polyolefin compositions and more particularly to such compositions which are halogen-free and flame retardant, and to shaped articles made from them.

15

Background Discussion:

Polyvinyl chloride (PVC) products have been on the market for many years and are commonly used in a large variety of applications. With the trend toward a chlorine-free environment, certain market segments such as the construction and wires and cables industries are in need of an alternative to PVC. Several halogen-free flame-retardant compounds are already available on the market but require difficult mixing processes. These compounds often need to be produced by specialized compounders, as the wire and cable and floor tile producers, themselves, often do not have the expertise.

For wire and cable applications, halogen-free flameretardant materials are desirable to provide both
insulation and jacketing in low-voltage cables in areas
where it is necessary to avoid the generation of
hazardous gases in the event of fire. Such areas where
halogen-free low-voltage cables are useful include
hotels, hospitals, schools, theaters and other such
public spaces.

Important characteristics for jacketing materials is that they are highly flame retardant, good heat performance and good physical properties.

5 U.S. Patent Nos. 4,948,669, 4,430,468, 4,434,258, 4,673,620, 4,701,359 disclose PVC-free compositions that are suitable for use as coatings for electrical cables. These compositions contain several components that are similar to those described herein, but lack, i.a., the terpolymer described herein.

Summary of the Invention

According to the present invention there is provided a

15 flame retardant, halogen-free polymer composition
comprising a blend of

office field from 1174 1 3 has been

the that the time are and the

20

30

- (1) ethylene vinyl acetate carbon monoxide terpolymer containing 30-90% by weight ethylene, 10-70% by weight vinyl acetate and 1-40% by weight carbon monoxide;
- (2) an ethylene vinyl acetate or polyolefin selected from the group consisting of (a) ethylene vinyl acetate containing 25-90% by weight ethylene and 10-75% by weight vinyl acetate, (b) a linear low density polyethylene, (c) a low density polyethylene, (d) a very low density polyethylene and (d) a high density polyethylene; and mixtures thereof;

(3) an ethylene vinyl acetate or polyolefin selected from the group consisting of (a) ethylene vinyl acetate containing 25-90% by weight ethylene and 10-75% by weight vinyl acetate, (b) a linear low density polyethylene, (c) a low density polyethylene, (d) a very low density polyethylene and (d) a high density polyethylene; and mixtures thereof; each of which is grafted with 0.05-3 % by weight of a carboxylic acid or an anhydride thereof; and

35

(4) an inorganic filler.

Common additives which may be included in the composition of the present invention include antioxidants, titanium dioxide (for UV resistance and to give a white color to the product), processing aids like zinc stearate and UV stabilizers.

10 <u>Detailed Description of the Invention</u>

The present invention relates to flame retardant, halogen-free thermoplastic polymer blends which are useful in wire and cable coatings or in sheet form such 15 as for use in floor tiles. These blends generally are formed by combining an ethylene vinyl acetate carbon monoxide (EVACO) terpolymer, an ethylene vinyl acetate (EVA) copolymer or polyolefin selected from EVA copolymer, a linear low density polyethylene, a low 20 density polyethylene, a very low density polyethylene, a high density polyethylene and mixtures thereof , an ethylene vinyl acetate (EVA) copolymer or polyolefin selected from EVA copolymer, a linear low density polyethylene, a low density polyethylene, a very low 25 density polyethylene, a high density polyethylene and mixtures thereof, each of which is grafted with a carboxylic acid or anhydride thereof, and an inorganic filler.

Polymer blends according to the present invention can be formed into wire and cable coatings or sheet form for uses such as for floor tiles, and have many properties comparable to polyvinyl chloride (PVC) containing blends, but are free from halogen.

Unless otherwise stated, percentage weight ranges for each of the components in the composition of the present invention are calculated exclusive of any additives which may be present.

The EVACO terpolymer (component (1)) useful in this invention preferably contains 30-90% by weight of ethylene, 10-70% by weight of vinyl acetate and 1-20% by weight of carbon monoxide, more preferably 55-65% by weight of ethylene and 20-30% by weight of vinyl acetate and 5-15% by weight carbon monoxide. In general, these EVACO's have a melt flow index (MFI) in the range of 1-50 g/10 min., preferably in the range of 10-40 g/10min. as determined by ASTM D-1238 (measured at 2,16 kg and 190 °C) and are well-known in the art.

Component (1) preferably comprises 1-60% by weight of the composition of the present invention, more preferably 5-15% by weight, still more preferably 5-15% by weight.

thin tast thin mile is the tast tast

į. ž

13

IU

ijŢ

30

The EVA copolymer when used as component (2) in this invention preferably contains 25-90% by weight of ethylene and 10-75% by weight of vinyl acetate, more preferably 55-75 % by weight of ethylene and 15-30 % by weight of vinyl acetate. In general, these EVA's have a melt flow index (MFI) in the range of 0.05-100 g/10 min., preferably less than 50 g/10min. as determined by ASTM D-1238 (measured at 2,16 kg and 190 °C) and are well-known in the art.

The polyolefins when used as component (2) in general will have a melt flow index (MFI) in the range of 0.05-100 g/10 min., preferably less than 50 g/10min. as determined by ASTM D-1238 (measured at 2,16 kg and 190 °C) and are well-known in the art.

Component (2) preferably comprises 1-50% by weight of the composition of the present invention, more preferably 5-25% by weight, still more preferably 10-20% by weight.

Component (3) is as defined as for component (2), but is further grafted with 0.05-3 % by weight of a carboxylic acid or anhydride thereof, preferably maleic anhydride.

5

Component (3) preferably comprises 1-40% by weight of the composition of the present invention, more preferably 1-15% by weight, still more preferably 3-10% by weight.

10 Component (4) is an inorganic filler. Suitable inorganic fillers are known in the art; preferred ones will also possess flame retardant characteristics. Specific, preferred inorganic fillers include aluminum trihydrate, magnesium hydroxide, calcium carbonate, calcinated clay, talcum, mica, zinc borates and mixtures thereof.

to carcum, mica, zinc boraces and mixtures chereor.

Component (4) preferably comprises 20-85% by weight of the composition of the present invention, more preferably 50-75% by weight, still more preferably 60-70% by weight.

20

i, Ti

Mar Suff Suit

ļ: Ā

ΪIJ

The grafted moities of component (3) tend to react with the inorganic filler of component (4) (c.f. K. Hausmann, V. Flaris, Polymers & Polymer Composites Vol. 5, No 2, 1997 p 113 ff. This leads to further compatibilization of the composition. Compositions with higher levels of compatibilization have higher mechanical strength, which allow for higher levels of inorganic filler and thus, compositions with higher flame retardancy.

In addition to its polymer and flame retardant filler components, the composition of the present invention can be blended with common additives such as antioxidants, UV stabilizers, lubricants (e.g., oleamide), antiblocking agents, antistatic agents, waxes, pigments, titanium

dioxide, talc and other processing aids (e.g., zinc stearate) known in the polymer compounding art. The additives may comprise up to about 10 weight percent of the total composition based on polymer components, flame retardant fillers plus additives.

THE CASE OF REST AND THE SECOND SECON

The blends of the invention can be prepared by mixing the polymeric ingredients flame retardant fillers and optional additives by use of conventional masticating equipment, for example, a rubber mill, Brabender Mixer, Banbury Mixer, Buss-ko kneader, Farrel continuous mixer or twin screw continuous mixer. Mixing times should be sufficient to obtain homogeneous blends and a proper reaction between maleic anhydride groups and the flame

retardant fillers (component (4)). Typically, mixing times of about 5 minutes and mixing temperatures of 160 °C are satisfactory. If the polymer blend is non-homogeneous, additional mixing is required.

15 The invention can be further understood by the following examples in which parts and percentages are by weight or in parts per hundred rubber (phr) and temperatures are in degrees Celsius.

20 Examples 1-4

Legend

MFI = melt flow index

25 EVACO = ethylene vinyl acetate carbon monoxide EVA = ethylene vinyl acetate

EVA+MAH = ethylene vinyl acetate grafted with maleic anhydride

HDPE+MAH = high density polyethylene grafted with maleic
anhydride

ATH = aluminum trihydrate

MAH = maleic anhydride

Procedure

35

30

A blend is prepared by melt-compounding the following components in the proportions set forth in Table 1 below.

- EVACO (71.5% ethylene, 20.5% vinyl acetate and 8% carbon monoxide) having a MFI (190°/2.16 kg) of 15
- EVA (72% ethylene and 28% vinyl acetate) having a MFI (190°/2.16 kg) of 3.0
- 5 EVA+MAH (72% ethylene and 28% vinyl acetate grafted with 1.5 % MAH) having a MFI (190°/2.16 kg) of 1.4
 - HDPE+MAH (grafted with 0.9 % MAH) having a density of 0.955 g/cc and a MFI (190°/2.16 kg) of 2.0
- VLDPE having a density of 0.902 g/cc and a MFI
 10 (190°/2.16 kg) of 1.0
 - antioxidant phenolic type available under the name IRGANOX 1010 from Ciba Specialty Chemicals

Melt compounding is carried out on a two roll mill with

15 batches from 100 grams at 150-170 °C for ca. 5 minutes.

The milled product is formed into a testing plaque in a hydraulic press at 150-170 °C for 5 minutes. Afterwards stress-strain testing (ASTM D-412), Limited Oxygen Index i.e. LOI (ASTM D 2863) and Knife Penetration at 80 and 90

20 °C (IEC 540 Item 10.1) are carried out. Results are shown in Table 1.

Table 1

25

	Example numbers	1	2
	EVACO	10	10
	EVA	16	13
30	EVA+MAH	9	4
	HDPE+MAH	_	4
	VLDPE	_	4
	ATH	64.7	64.7
	Antioxidant	0.3	0.3
35	Tensile strength (MPa)	14.6	15.7
	Tensile elongation (%)	150	140
	Knife Penetr. at 80 °C (%)	80	0
	Knife Penetr. at 90 °C (%)	100	0
	LOI (%)	38	35

One can see that the formulation containing HDPE+MAH and VLDPE show particularly lower knife penetration values (better heat performance) but lower flame retardancy than the formulation without. For some wire and cable applications, heat performance can be of major importance while in others flame retardancy is the most important criteria.

Man And Street and Street Street

South Head Will Will mile Half

Claims

 A flame retardant, halogen-free polymer composition comprising a blend of

5

(1) ethylene vinyl acetate carbon monoxide terpolymer containing 30-90% by weight ethylene, 10-70% by weight vinyl acetate and 1-40% by weight carbon monoxide;

10

15

- (2) an ethylene vinyl acetate or polyolefin selected from the group consisting of (a) ethylene vinyl acetate containing 25-90% by weight ethylene and 10-75% by weight vinyl acetate, (b) a linear low density polyethylene, (c) a low density polyethylene, (d) a very low density polyethylene and (d) a high density polyethylene; and mixtures thereof;
- 20 (3) an ethylene vinyl acetate or polyolefin selected from the group consisting of (a) ethylene vinyl acetate containing 25-90% by weight ethylene and 10-75% by weight vinyl acetate, (b) a linear low density polyethylene, (c) a low density polyethylene, (d) a very low density polyethylene and (d) a high density polyethylene; and mixtures thereof; each of which is grafted with 0.05-3 % by weight of a carboxylic acid or an anhydride thereof; and

30

- (4) an inorganic filler.
- A blend according to claim 1 wherein component (1) comprises 1-60 % by weight of the blend, component (2)
 comprises 1-50 % by weight of the blend, component (3) comprises 1-40 % by weight of the blend, and component (4) comprises 20-85% by weight of the blend.

- 3. A blend according to claim 1 wherein component (1) comprises 5-25% by weight of the blend, component (2) comprises 5-25% by weight of the blend component (3) comprises 1-15% by weight of the blend, and component (4) comprises 50-75% by weight of the blend.
- 4. A blend according to claim 1 wherein component (1) comprises 5-15% by weight of the blend, component (2) comprises 10-20% by weight of the blend component (3)
 10 comprises 3-10% by weight of the blend, and component (4) comprises 60-70% by weight of the blend.

5

Are the first that the first the first that

į. d.

1.2

- 5. A blend according to claim 1 wherein component (4) is aluminum trihydrate, magnesium hydroxide, calcium carbonate, calcinated clay, talcum, ammonium polyphosphate or a mixture thereof
 - 6. A shaped article formed from a blend according to claim 1.

DECLARATION and POWER OF ATTORNEY

									
As a below-named inventor, I hereby declare that:									
,	My residence, post office address and citizenship are as stated below next to my name.								
I believe I am the o	riginal, first and sole inventor (if on	ly one n	ame is listed belo	w) or an original, first a	nd joint inventor (if plural nar	nes are			
listed below) of the	listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: FLAME RETARDANT POLYOLEFIN COMPOSITIONS								
					IIIONS				
	which is attached hereto unless the								
was filed on	23 JULY 1998 as U.S. A	Applicati	ion No	or PCT Inte	mational Application No.				
	S98/15229 and was amended			applicable).					
I hereby state that I amendment ref	have reviewed and understand the derred to above.	contents	of the above iden	tified specification, incl	luding the claims, as amended	by any			
	duty to disclose information which i								
I hereby claim foreign priority benefits under 35 U.S.C. § 119(a)-(d) or § 365(b) of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.									
Application No.			Filing Da	te	Priority Claimed (Yes/No)				
97202335.2	EP EP		25 JULY	1997	Yes				
I hereby claim the	penefit under 35 U.S.C. § 119(e) of	any Unit	ted States Provision	onal Application(s) liste	ed below.				
	U.S. Provisional Application				.S. Filing Date				
I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s), or § 365(c) of any PCT International Application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application or PCT International Application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose information which is known to me to be material to patentability as defined in 37 CFR § 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application. Application No. Filing Date Status (patented, pending or abandoned)									
POWER OF ATT business in the Pate	ORNEY: I hereby appoint the follogent and Trademark Office connected	wing at	torney(s) and/or a	gent(s) the power to pro	osecute this application and tra	ansact all			
	ICIA L. KELLY				9,247				
Send corresponden	ce and direct				Tel. No.				
telephone calls to:		E. I. d	lu Pont de Nemo	urs and Company	(302) 992-6743				
PATRI	CIAI KELIV	Legal Wilmi	- Patents ngton, DE 19898, U.S.A. Fax No.						
PATRICIA L. KELLY			(302) 992-2953						
I hereby declare the	at all statements made herein of my	own kno	wledge are true a	nd that all statements m		are			
believed to be true; punishable by fine	I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.								
1	11)		INVENTOR(S)					
Full Name	Kast Name		First Name		Middle Name				
of Inventor	GARCIA DURAN Signature (please sign full name):	10-	JUAN	<u> </u>	ANTONIO				
	Signature (picase sign full name):	1	- fuen-	aulonoGam	Date: 20.06.20	> >>>			
Residence &	City	γ	State or Foreign C	ountry	Country of Citizenship				
Citizenship Post Office	Post Office Address	<u> </u>	SWITZERLA	ND	State or Country	Zip Code			
Address	26 AV. DE L'AMANDOLIE	R	City GENEVE		SWITZERLAND	CH- 1208			
Full Name	Last Name		First Name		Middle Name				
of Inventor ROLLAND			LOIC		PIERRE				
	Signature (please sign full name):	Lo	ic Rol	land	Date: June 15	, 1000			
Residence &	City	• •	State or Poreign	ountry /	Country of Citizenship				
Citizenship	DIVONNE-LES-BAINS		FRANCE	14	FR	T =			
Post Office Address	Post Office Address RESIGENCE METNA, 234	4 V.	DIVONNE-L	ES-RAINS	State or Country FRANCE	Zip Code F-01220			
41UUI C55	DE LA GRANDE, CHAMPA			AND INITIAN		1 -01220			
									

_	Additional	Inventors are	being named	l on separatel	y numbered	sheets	attached	hereto
---	------------	---------------	-------------	----------------	------------	--------	----------	--------

The first time and the first time and the first time and the first time and the first time and

their circus areas many game, areas are some or the circus areas areas are areas from the circus areas are areas.

United States Patent & Trademark Office

Office of Initial Patent Examination -- Scanning Division



Application deficiencies were found during scanning:

Page(s) of Certificate of Mailing were not present for scanning. (Document title)

Page(s) of were not present for scanning. (Document title)

☐ Scanned copy is best available.